

# SmartSource® Micro Elite

The Secure Choice®



The SmartSource Micro Elite scanner is an extremely compact, low-cost scanner optimized for low-volume remote deposit capture applications. Like all scanners in the Digital Check® portfolio, the SmartSource Micro Elite provides industry-leading quality and performance.



## ID SCANNING

The Micro Elite features dual 600 dpi image sensors that produce high-resolution images in either full color or grayscale. It can also scan rigid items such as ID and health insurance cards. Its open-top track allows capture of items up to 4.25 inches in height.

## SINGLE-FEED OPERATION & SMALL FOOTPRINT

The Micro Elite is the smallest check scanner in its class, taking up very little desktop or teller counter space and can handle checks as fast as you can feed them into the device.

## KEY FEATURES & BENEFITS

- **Small Footprint for a More Efficient Workspace**
- **ID Card Scanning with 600 dpi Image Sensors**
- **Automated Cleaning with Smart Button Indicator**
- **Open-Top Track for Easy Access**

## AUTOMATED CLEANING

An LED light alerts the user when it is time to clean. The user then simply presses the Smart Button three times to activate cleaning mode, inserts a fresh cleaning card, and the scanner performs a unique cleaning sequence that scrubs the track and cleans the image sensors.



## Affordable and Cost-Effective

The SmartSource Micro Elite is built with the quality of our batch-feed scanners, but with a much smaller footprint and at a significantly lower cost. So, whether you need an RDC scanner in North America or a scanner at the services desk to scan IDs and checks when opening an account, the Micro Elite is the scanner for you!



## Incorporating Decades of Technology

The Micro Elite is compatible with and easily integrated into applications developed for the SmartSource Professional or Elite series scanners. If you're already using other SmartSource scanners, integration and certification is a much more streamlined process. The Micro Elite uses all the latest Digital Check technology, including our industry-leading MICR, OCR, barcode recognition, color image capture, and image processing algorithms.



## Industry-Leading Image & MICR Capture

The Micro Elite uses 600 dpi image sensors and applies thresholding to create high-resolution images resulting in superb CAR/LAR read rates. Our top-of-the-line MICR read heads coupled with optical recognition offer a proven and reliable defense against ambiguous characters and out-of-spec documents.



630 Dundee Rd., Suite 210 • Northbrook, IL 60062 • Tel: 847.446.2285 • Fax: 847.441.5507 • [www.digitalcheck.com](http://www.digitalcheck.com)

Digital Check, the Digital Check Logo, SmartSource and The Secure Choice are registered US trademarks of Digital Check Corp.

All other product names mentioned herein may be trademarks of their respective owners.

© 2026 Digital Check Corp.

2026.03.04

# SmartSource<sup>®</sup> Micro Elite

## Scanner Specifications



### Scanner Dimensions

Height: 7.01 in (17.8 cm)  
Width: 4.17 in (10.6 cm)  
Length: 6.97 in (17.7 cm)  
Weight: 2.9 lbs. (1.32 kg)

### Document Input and Output Pockets

Entry Pocket: Single feed scanner (1 item at a time)  
Exit Pocket: 1 item

### Document Handling

Document Height: 2.00 to 6.00 in (5.08 to 15.24 cm)  
Image Capture Height: Up to 4.25 in (10.80 cm)  
Document Length: 2.90 to 9.25 in (7.37 to 23.5 cm)  
Document Weight: 16 to 28 lb (60 to 105 gsm)  
Document Thickness: 0.0032 - 0.0058 in (0.081 - 0.147 mm)  
Accepts 12 lb (45 gsm) paper at a reduced throughput and pocket capacity  
Alternate Input: ID cards and items up to 0.030 in (0.76 mm) thick, and items taller than 6.00 in (15.24 cm)  
ID Card Capture (supported by application)

### MICR/OCR Recognition

E13B MICR/OCR combine read  
CMC7 MICR read  
OCR-A, OCR-B, E13B, and 1D barcode fonts supported  
Two (2) 0.50 inch OCR scan bands provided  
96 characters per scan band

### Image Sensor

Resolution: 600 dpi  
Light Source: Tri-Color LEDs

### Image Compression Standards

CCITT Group 4 (bi-tonal images)  
JPEG Baseline (gray level images)  
JPEG Compression (color images)

### Productivity Functions (Smart Button)

Combined power switch  
Feeder start/stop  
SmartClear button  
Automated cleaning mode  
LED status light

### Connectivity

High-speed USB 2.0 cable and power supply included

### Application Programming Interfaces (API)

SmartPVA API

### Supported Operating Systems

Windows 11/10 (x86 and x86-64)

### Standard Warranty

One year pursuant to Digital Check Corp.'s limited product warranty

### Power Requirements

100-240 VAC @ 50/60 Hz  
Operating Power: 20 W  
Standby Power: 3 W

### Environmental

Operating Temperature: 60° - 90° F (15° - 32° C)  
Operating Humidity: 35 - 85% non-condensing

### Certifications

**Safety:**  
UL, cUL, CE, BIS

### Emissions:

FCC: Class B  
ICES-003  
CE

### Power Supply Efficiency:

DOE Level VI  
RoHS Compliant

### Part Numbers

SSM1-MICROELITE-NOIJ (SmartSource Micro Elite - Non-Inkjet)

